

MIPOLAM® 150

DESCRIPTION

| | | | | |
|-------------------------|--------------------|------------------|----------|------|
| Total thickness | ISO 24346 (EN 428) | mm | 1.5* | 2 |
| Weight | ISO 23997 (EN 430) | g/m ² | 2500 | 3300 |
| Width / Length of sheet | ISO 24341 (EN 426) | cm / lm | 200 / 20 | |

CLASSIFICATION

| | | | | |
|------------------------------|--------------------|-------|-----------------------------------|--|
| Norm / Product specification | - | - | ISO 10581 (EN 649) | |
| European classification | ISO 10874 (EN 685) | class | 23 - 31 / 34 - 43 | |
| Fire rating | EN 13 501-1 | class | Bfl-s1 | |
| Static electrical propensity | EN 1815 | KV | <2 | |
| Electrical resistance | EN 1081 | Ω | 10 ⁹ -10 ¹⁰ | |
| Slip resistance dry | EN 13893 | - | ≥0.3 | |
| Slip resistance wet | DIN 51130 | class | R9 | |

PERFORMANCES

| | | | | |
|---|----------------------|-----------------|-------------|--|
| Wear resistance | EN 660.2 | mm ³ | ≤7.5 | |
| Wear group | EN 649 | group | M | |
| Type binder content | ISO 10581 | type | II | |
| Dimensional stability | ISO 23999 (EN 434) | % | ≤ 0.4 | |
| Residual indentation | ISO 24343-1 (EN 433) | mm | ≈0.05 | |
| Castor chair test | ISO 4918 (EN 425) | - | OK | |
| Thermal conductivity | ISO 10456 (EN 12524) | W/(m.K) | ≈0.25 | |
| Colour fastness | ISO 105 - B02 | degree | ≥ 6 | |
| Chemical products resistance | ISO 26987 (EN 423) | - | OK | |
| Anti-bacterial and fungicidal treatment | - | - | OK | |
| Surface treatment | - | - | PUR Protect | |
| Color number | - | - | 22 | |

ENVIRONMENT / INDOOR AIR QUALITY

| | | | | |
|--------------------|---------------|-------------------|-------------|--|
| TVOC after 28 days | ISO 16000 - 6 | µg/m ³ | < 10 | |
| Certification | - | - | Floorscore® | |

CE MARKING

| | | | |
|----|----------|---|--|
| CE | EN 14041 | - | |
| | | | |

* Special order, minimum quantities needed

MIPOLAM® 150 is a durable, high performing flexible homogeneous multipurpose flooring suitable for most types of heavy traffic areas. It benefits from PUR Protect surface treatment with excellent cleaning characteristics, improved resistance to scratching and scuffing.

MIPOLAM® 150 is recommended for public, institutional and commercial buildings where ease of maintenance and long life under heavy traffic are required.

Gerflor Don't forget our complementary ranges!

Handrails

Wall Coverings & Protections

Entrance mats

Skirtings & Profiles

MIPOLAM® 150, LESS SPEAKING FOR MORE ACTIONS

COMPOSITION
100% REACH compliant
FREE of formaldehyde
FREE of heavy metals
FREE of solvent

RECYCLED CONTENT
25% average recycled content
100% REACH compliant recycled content

RECYCLABILITY
100% recyclable product

INDOOR AIR QUALITY
TVOC emissions between 10 and 100 times better than norms requirements
Floorscore certified
No formaldehyde emission

INSTALLATION
Innovative adhesive free installation systems

WELLNESS
Health: Antibacterial activity (inhibits growth > 99%)

Be connected!

www.gerflor.com

#Gerflor