


Mipolam® Ambiance Ultra™ is a homogeneous pressed compacted floorcovering in sheet, with non-directional design, colour dyed as a raw mixture to ensure even color throughout the thickness and a matt finish. Its surface is densely compacted for improved wear and ease of maintenance.

It is treated with Evercare™, the latest improvement in polyurethane special maintenance treatment obtained by UV laser crossing-linking. Evercare™ avoids staining of chemical products, like betadine, eosin, or anti-bacterial hand gel and increases the durability of the flooring. No wax for life!

Mipolam® Ambiance Ultra™ incorporates bacteriostatic and fungistatic actions. The flooring complies with the EN 649 (34-43) and has a Group T wear rating. It is suitable for very heavy traffic areas.

Mipolam® Ambiance Ultra™ is available in a wide pallet of 50 classic and trendy colors.

MIPOLAM® AMBIANCE ULTRA™

DESCRIPTION			
Total thickness	ISO 24346 (EN 428)	mm	2
Weight	ISO 23997 (EN 430)	g/m ²	2750
Width of sheet	ISO 24341 (EN 426)	cm	200
Length of sheet	ISO 24341 (EN 426)	lm	20
CLASSIFICATION			
Norm / Product specification	-	-	ISO 10581(EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13 501-1	class	Bfl-s1
Static electrical propensity	EN 1815	KV	< 2
Electrical resistance	EN 1081	Ω	10 ⁹ -10 ¹⁰
Slip resistance dry	EN 13893	-	≥ 0.3
Slip resistance wet	DIN 51130	class	R9
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group	EN 649	group	T
Type binder content	ISO 10581	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4
Residual indentation	ISO 24343-1 (EN 433)	mm	≈ 0.03
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	≈ 0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK
Anti-bacterial and fungicidal treatment	-	-	OK
Surface treatment	-	-	Evercare™
Anti-bacterial activity (E. coli - S. aureus - MRSA) ⁽¹⁾	ISO 22196	-	>99 % Inhibits growth
Color number	-	-	50
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10
Certification	-	-	Floorscore™
CE MARKING			
CE	EN 14041	-	

(1) The implementation of an effective cleaning regime is the most important defence against infections.

Gerflor Don't forget our complementary ranges!



MIPOLAM® AMBIANCE ULTRA™, LESS SPEAKING FOR MORE ACTIONS

 <p>COMPOSITION 100% REACH compliant</p>	 <p>INDOOR AIR QUALITY 100 times lower than norm requirements (TVOC < 10µg/m³ after 28 days)</p>	 <p>RECYCLED CONTENT 100 % REACH compliant recycled content</p>	 <p>RECYCLABILITY 100 %</p>	 <p>LCA Eco-designed according to a product specific life cycle analysis</p>	 <p>WELLNESS Walking comfort: < 75 dB</p>
--	--	---	---	--	--

Be connected!



#Gerflor



www.gerflor.com

Gerflor
the flooring group

GERFLOR ASIA Tel.: + 86-21-63578818